

 HT SERIES™ SNOWPLOW



HT SERIES™

HT SERIES™



HT SERIES™



THE ORIGINAL TRIP-EDGE DESIGN Only the edge of the blade trips back when encountering an obstacle. This system is much less jarring than a full-trip blade and, because the blade stays upright, plowed snow remains in front of the blade.



STORM GUARD™ powder coating process provides industry-best protection against wear and rust.

As half-ton pickup truck manufacturers reduce vehicle weight in their quest for increased fuel efficiency, plowers struggle to find a legitimate, rugged, hard-working snowplow that matches their vehicle specifications.

That's why Fisher Engineering developed the sleek new HT Series™ snowplow. Targeted specifically for today's half-ton 4WD pickup trucks, the FISHER® HT Series snowplow is a full-size, full-featured snowplow with the strength to handle standard-duty commercial, institutional and extended-use homeowner applications.

And since it's built by Fisher Engineering, it's backed by a 60-year heritage of top product performance and unmatched customer loyalty.



The proven Minute Mount® 2 System is simple, reliable and fast. The new HT Series snowplow features a handy push-bar that makes mounting even easier. This mount features multiplexed electrical technology.



Covered hydraulic system provides protection from the elements.



FISHER INTENSIFIRE™ halogen headlamps feature state-of-the-art reflector optics for a smooth, wide beam pattern that illuminates the entire plowing surface.



- 75-degree attack angle provides improved scraping and better back dragging.
- 15-1/2-inch curl radius improves snow rolling action.

- 6 vertical ribs and a full-length horizontal tube provide extra stability and strength to the core of the blade.
- A pair of vertical compression trip springs deliver trip-edge protection.



Control options include the hand-held Fish-Stik® or a compact joystick control.

Optional accessories include 3/8" and 1/2" steel or 1" poly cutting edges, cast iron shoes, curb guards and both rubber and steel snow deflectors.



Exclusive scrape lock feature hydraulically locks the blade down for clean scraping and back dragging.

Blade Width	Blade Height	Blade Gauge	Trip Springs	Ribs	Angling Rams	Plowing Width (full angle)	Approx. Weight (less mount)	Wear Shoes (cast iron)	Optional Cutting Edge
7'-6"	27"	14	2	6+Tube	1-1/2" x 8"	6'-7"	414#	optional	3/8" x 6" steel 1/2" x 6" steel 1" x 6" poly



See our separate full-line snowplow and spreader catalogs for the complete FISHER® snow and ice control lineup!



Fisher Engineering reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Fisher Engineering or the vehicle manufacturer may require or recommend optional vehicle equipment for snow removal. Do not exceed vehicle ratings with a snowplow. This product is manufactured under the following US patents: 4,999,935; 5,353,530; 5,420,480;



5,638,618; 5,899,007; 6,253,470; 6,408,549; 6,944,978; RE35,700; CAN patents 2,060,425; 2,184,922; 2,229,783; 2,356,036; and other patents pending. Fisher Engineering offers a limited warranty for all snowplows and accessories. See separately printed page for this important information. The following are registered(®) or unregistered(™) trademarks of Douglas Dynamics, L.L.C.: FISHER®, Fish-Stik®, INTENSIFIRE™, Minute Mount® 2, POLY-CASTER™, STORM GUARD™.

FISHER ENGINEERING • 50 GORDON DRIVE • ROCKLAND, MAINE 04841 • www.fisherplows.com